

ByciGolf™

INSTALLATION INSTRUCTIONS

Golf Pull Cart Hitch for Bicycle without Rear Rack



INCLUDED IN THIS GUIDE



Assembly Recommendations
List of Components
Figures & Instructions

ASSEMBLY RECOMMENDATIONS

You can use screws or tightening knobs to fasten the different components.

For parts assembly, we recommend the use of a wrench which allow you to control the tension more easily.

When tightening the different components, on a scale of 0 to 10, it is preferable to have a tension of 6. This will make it easier for you to make adjustments throughout the installation.



LIST OF COMPONENTS

- | | | | |
|----------|--------------------------|-----------|-------------------------|
| 1 | BYCIGOLF rear rack | 8 | ¼ screw x 4 |
| 2 | BYCIGOLF cart hitch | 9 | 1 ½ screw x 2 |
| 3 | 2 rack mounting branches | 10 | 1 ¼ screw x 4 |
| 4 | 2 female attachments | 11 | ¼ tightening knobs x 10 |
| 5 | 2 male attachments | 12 | ½ tightening knobs x 2 |
| 6 | 2 saddle post clamps | 13 | Square tube connector |
| 7 | 10 hex nuts | | |



Figure 1A

Secure a male and female attachments with tension 4 on the kickstand side, allowing them to slide along the seatstays. Next, attach $\frac{1}{4}$ tightening knob and tighten the clamp with tension 9.



Figure 1B

Slide the clamp so that the vertical stem of the rack mounting branch is perpendicular to the ground and slightly in front of the bike's rear axle. Tighten securely (tension 10) to the seatstays.



Figure 2

Once the clamp on the kickstand side is securely fastened to the tension 10, remove the rack mounting branch.



Figure 3A

Secure a male and female attachments with tension 4 on the chain side of the bike in line with the clamp attached in the previous step on the kickstand side. (Figure 3A & 3B)



Figure 3B



Figure 4

Attach the two rack mounting branches to the BYCIGOLF rear rack with the four $\frac{1}{4}$ screws.



Figure 5A

Fasten the rack mounting branches to the clamps.



Figure 5B



Figure 5C



Figure 6

Attach the square tube connector to the saddle post clamps.



Figure 7

Insert the square tube connector into the BYCIGOLF rear rack.



Figure 8A

Making sure the rack is level with the ground, stretch the tube connector to the saddle post. Next, place the clamps around the saddle post and tighten the knob of the BYCIGOLF rear rack where the connector is inserted, then to the saddle post clamps.



Figure 8B

An alternative to the previous step is to remove the saddle. This method can make it easier to attach clamps to the saddle post.



Figure 9

Insert the BYCIGOLF cart hitch into the appropriate hole in the BYCIGOLF rear rack.



Figure 10

Then tighten the knob until the cart hitch stops moving.



Figure 11

Attach the BYCIGOLF cart hitch to your golf bag pull cart.



Figure 12

Install the golf bag on the golf bag pull cart.

HOW TO REACH US



BYCIGOLF

4295, Boul. St-Elzéar Ouest
Laval, Québec, H7P 4J3

SPECIAL ORDERS

Tel: +1 450-987-1957

BYCIGOLF.CA